




Three Phase Hybrid Inverter

SUN- 25 / 30 / 40 / 50 K-SG01HP3-EU-BM2/3/4



- 100** 100% unbalanced output, each phase; Max. output up to **50%** rated power
-  DC couple and AC couple to retrofit existing solar system
- 10** Max. 10pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- 100** Max. charging/discharging current of 100A
- H** High voltage battery, higher efficiency
- 6** 6 time periods for battery charging/discharging
-  Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-25K-SG01HP3 -EU-BM2	SUN-30K-SG01HP3 -EU-BM3	SUN-40K-SG01HP3 -EU-BM4	SUN-50K-SG01HP3 -EU-BM4
Battery Input Data				
Battery Type	Li-Ion			
Battery Voltage Range (V)	150~800			
Max. Charging Current (A)	50+50			
Max. Discharging Current (A)	50+50			
Number of battery input	2			
Charging Strategy for Li-Ion Battery	Self-adaption to BMS			
PV String Input Data				
Max. DC Input Power (W)	32500	39000	52000	65000
Max. DC Input Voltage (V)	1000			
Start-up Voltage (V)	150			
MPPT Range (V)	200-850			
Min. DC Input Voltage (V)	150			
Full Load DC Voltage Range (V)	450-850	360-850	360-850	450-850
Rated DC Input Voltage (V)	600			
PV Input Current (A)	36+36	36+36+36	36+36+36+36	
Max. PV I _{sc} (A)	55+55	55+55+55	55+55+55+55	
No. of MPP Trackers	2	3	4	
No. of Strings per MPP Tracker	2			
AC Output Data				
Rated AC Output and UPS Power (W)	25000	30000	40000	50000
Max. AC Output Power (W)	27500	33000	44000	55000
AC Output Rated Current (A)	38	45.6	60.8	75.8
Max. AC Current (A)	50	60	70	83.3
Max. Continuous AC Passthrough (A)	150			
Peak Power (off grid)	1.5 time of rated power, 10 S			
Generator input/Smart load /AC couple current (A)	38 / *150 / 38	45.6 / *150 / 45.6	60.8 / *150 / 60.8	75.8 / *150 / 75.8
Power Factor	0.8 leading to 0.8 lagging			
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380, 230/400Vac			
Grid Type	Three Phase			
DC injection current (mA)	<0.5%1n			
Efficiency				
Max. Efficiency	97.60%			
Euro Efficiency	97.00%			
MPPT Efficiency	99.90%			
Protection				
Integrated	PV Input Lightning Protection, Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection			
Output Over Voltage Protection	DC Type II/AC Type III			
Certifications and Standards				
Grid Regulation	CEI 0-21, VDE-AR-N 4105, NRS 097, IEC 62116, IEC 61727, G99, G98, VDE 0126-1-1, RD 1699, C10-11			
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			
General Data				
Operating Temperature Range (°C)	-40~60°C, >45°C derating			
Cooling	Smart cooling			
Noise (dB)	<45 dB			
Communication with BMS	RS485; CAN			
Weight (kg)	60			
Size (mm)	560.5W×837H×319D			
Protection Degree	IP65			
Installation Style	Wall-mounted			
Warranty	5 years			